


TKF VALULIFT® CONTINUOUS VERTICAL CONVEYORS



TKF now offers a revolutionary new light-duty vertical conveyor. VALULIFT® incorporated economical modular design for simplified assembly, efficient high speed operation and low maintenance.

Standard Features

- Uses 24 Volt DC control for optimum safety
- Unique platform design with construction of molded polymer flights with heavy duty connecting chain
- Lube free idler sprockets of hardened steel with sealed journal bearings
- Includes slider bed belt conveyor at infeed point, with integral safety guard and clutch brake
- Powered transition rollers at discharge point
- Power drive consists of shaft mounted reducer - no noisy chain drive requiring maintenance
- Totally enclosed construction with shroud type tunnel guards
- Smooth clean design



Lift Speed and Capacity

Net Lift (Ft)	Speed FPM		Capacity - Cartons/Min	
	Max	Min	Max	Min
8	118	40	25	3.5
10	118	40	26	2.9
12	118	40	27	2.5
14	118	40	27	2.3



Maximum Unit Load:

21" long x 16" wide x 22" height - 50 lbs.

Minimum Unit Load:

10" long x 4" wide x 1.5" height - 3lbs.

Standard Lifting Heights:

8' 0" - 10' 0" - 12' 0" - 14' 0"

(Other lifting heights available)

Feed/Discharge Points:

Infeed elevation - minimum 10",

Discharge elevation - maximum 20' 0"



TKF Conveyors
5298 River Road
Cincinnati, OH, 45233
513.241.5910

www.tkf.com